

# Snell

## ICS Series



### Down Firing..or..Front Firing

ICS, is for In-Cabinet Speaker. Placing conventional speakers in cabinets, or near corners or walls causes the sound to become cupped and chesty. Snell ICS speakers are referenced from our acclaimed "in-room" models, then re-engineered for the boundaries and conditions found in cabinets and millwork. Furthermore, the ICS models are hand-finished in black texture paint, ideal for these invisible locations.

The ICS Sub300, with its innovative mechanical design, can be either front or down firing. The cleverly designed enclosure allows the feet and 300 Watt amplifier to be repositioned so that the long-throw, 10" woofer can be placed firing downward, for a "slot grille" application, or forward firing when in millwork with a full faced grille. Derived from the Basis 300, the ICS Sub300 is a compact 15" cube, capable of first octave bass at levels 110dB, making it the perfect anchor for better home theater systems.

# ICS Sub300

Design	Bass Reflex, Powered Subwoofer
Frequency Response	25Hz-150Hz±3dB
Amplifier Power	300 Watts
Crossover	Variable 50-150Hz
Maximum Output @30Hz	110dB
Placement	Front Firing or Down firing, Frontwall Recommended
Drive Unit	Woofer: 10-inch Treated Paper Cone, 15mm Excursion
Inputs/Outputs	L/R Low Pass, Low/High Level Inputs, Full Range Input/Output
Controls	Front-Mounted Level Control
	Variable Low-Pass
	Phase Switch, 0 Degrees/ 180 Degrees
	On/Off, Auto On-Off Switch with Instant On, and Turn-Off Delay
Video Shielding	Optional
Dimensions	Height: 16.5-inches, includes feet (1.5-inches)
	Width: 15-inches
	Depth: 15-inches
Finishes	Cabinet: Black Painted MDF
	Most wood and paint finished available for an extra cost
	Grille: N/A
	<a href="http://www.snellacoustics.com">www.snellacoustics.com</a> 978-538-6262 978-538-6266fax